

08-29-00

A

**UTILITY  
PATENT APPLICATION  
TRANSMITTAL**

Attorney Docket No.

1135.ACT2.PT

First Inventor or Application Identifier

Sovine

Title

CLEARING TRAP

Express Mail Label No.

EL593619398US

**APPLICATION ELEMENTS and ACCOMPANYING APPLICATION PARTS**

Enclosed for filing, please find the following items:

1. ☒ Specification [Total Pages 23]
2. ☒ Drawing(s) [Total Sheets 7]  
☒ Informal ☐ Formal
3. ☐ Oath/Declaration, Power of Attorney, and Petition
  - a. ☐ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d)) (for continuation/divisional with Box 14 completed)
    - i. ☐ Deletion of Inventor(s): Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).
4. ☐ Small Entity Statement
  - a. ☐ Newly executed (original or copy)
    - i. ☐ For an independent inventor
    - ii. ☐ For a small business concern
    - iii. ☐ For a non-profit organization
  - b. ☐ Copy from a prior application (for continuation/divisional with Box 14 completed)
5. ☐ Assignment with cover sheet
6. ☐ Information Disclosure Statement (IDS)
  - a. ☐ PTO-1449
  - b. ☐ Copies of IDS citations
7. ☒ Return Receipt Postcard
8. ☐ Fees as calculated below: ☐ Check in the amount of \$\_\_\_\_\_

Address To:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, D.C. 20231

☒ This application is filed Missing Parts

			SMALL ENTITY		NON- SMALL ENTITY	
FOR	NO. FILED	NO. EXTRA	RATE	FEE	RATE	FEE
BASIC FEE				\$345		\$690
TOT. CLAIMS	-20 =		x 9 =	\$	x 18 =	\$
IND. CLAIMS	-03 =		x 39 =	\$	x 78 =	\$
MULTIPLE DEPENDENT CLAIMS PRESENTED			\$130		\$260	
ASSIGNMENT FILING FEE			\$40		\$40	
			TOTAL		TOTAL	

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b> <small>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</small>	Attorney Docket No.		1135.ACT2.PT
	First Inventor or Application Identifier		Sovine
	Title	CLEARING TRAP	
	Express Mail Label No.		EL593619398US

jc895 U.S. Pat  
09/650843  
08/28/00

- 9. ☐ Preliminary Amendment
- 10. ☐ English Translation Document *(if applicable)*
- 11. ☐ Certified Copy of Priority Document(s)
- 12. ☐ Microfiche Computer Program *(Appendix)*
- 13. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all necessary)*
  - a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identify of above copies

14. **If a CONTINUING APPLICATION**, check appropriate box, and supply the requisite information below and in a preliminary amendment:  
☐ Continuation    ☐ Divisional    ☐ Continuation-in-part (CIP)

*Prior application information:*  
 Serial No.: \_\_\_\_\_ Filing Date: \_\_\_\_\_  
 Examiner: \_\_\_\_\_ Group/Art Unit: \_\_\_\_\_

**For CONTINUATION or DIVISIONAL APPS only:** The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

15. Other items enclosed:

16. List of inventors/applicants:

Inventor	<u>H. Addison Sovine</u>	Citizenship	<u>USA</u>
Address	<u>P.O. Box 636, Provo, Utah 84603-0636</u>		
Inventor	_____	Citizenship	_____
Address	_____		
Inventor	_____	Citizenship	_____
Address	_____		

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b> <small>(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))</small>	Attorney Docket No.		1135.ACT2.PT
	First Inventor or Application Identifier		Sovine
	Title	CLEARING TRAP	
	Express Mail Label No.		EL593619398US

**17. CORRESPONDENCE ADDRESS**

Name Randall B. Bateman  
MORRISS, BATEMAN, O'BRYANT &  
COMPAGNI


Registration No. 37,774

Address 5882 South 900 East, Suite 300

City Salt Lake City State Utah Zip 84121 Country Salt Lake

Telephone (801) 685-2302 Facsimile (801) 685-2303

Signature



Date

8-28-00

**CERTIFICATE OF DEPOSIT UNDER 37 C.F.R. § 1.10**

I hereby certify that the items listed above in this transmittal sheet are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated below and is addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

Name: RANDALL B. BATEMAN

Date

8-28-00

Express Mail No.: EL 593619398 US

EXPRESS MAIL

ATTORNEY DOCKET NO. 1135.ACT2.PT

5

CLEARING TRAP

10

TO THE COMMISSIONER OF PATENTS AND TRADEMARKS:

15

Your petitioner, H. Addison Sovine, a citizen of the United States and resident of Utah, having a post office address at P.O. Box 636, Provo, Utah 84603-0636, prays that letters patent may be granted to him as inventor of the improvement in a Clearing Trap as set forth in the following

20

specification.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to a method of decelerating projectiles. More specifically, the present invention relates to an improved clearing trap for decelerating projectiles discharged when performing a clearing check to ensure that the gun is empty.

### 2. State of the Art

In order to maintain proficiency in the use of firearms, it is common for law enforcement officers and sportsmen to engage in target practice. Participants will typically shoot at targets which are placed before some type of bullet containment system. After passing through the target, the bullet is typically contained in a trap where the bullet may be retrieved and recycled. Such traps include total containment system wherein the bullet is received in a chamber, and less expensive berm traps in which the bullet is received by a bullet deceleration medium.

After a target shooter is finished, it is usually a requirement that he unload the weapon for transportation and/or storage. While it is easy to remove a magazine or other container holding the bullets, it is often difficult to

accurately determine if a bullet is contained in the chamber of the gun. Numerous people have been killed or injured when a gun which was believed to be empty discharged.

To prevent such accidents from occurring, it is common for the target shooter to use a clearing trap. A clearing trap is typically a small trap disposed near the main target range into which a gun is inserted and the trigger pulled. If the gun has been properly emptied, there will be no discharge and the user will be assured that the gun is empty. However, occasionally the gun will fire due to a round that was not properly removed from the chamber. Once the round is discharged, the user may pull the trigger again for assurance that the gun is empty. Once it is demonstrated that the gun is empty, the user may store or transport the gun.

While clearing traps are important to prevent accidental discharges, the presently available traps have several disadvantages. For example, in FIG. 1A there is shown a perspective view of a prior art clearing trap, generally indicated at 10. The clearing trap 10 has a cylindrical housing 14 which has a closed lower end 18 and an upper end 22 partially enclosed by a disk with an opening for receiving the barrel of a gun. The cylindrical housing is held at an angle of between about 45 and 70 degrees so that the user may hold

the gun in a comfortable position while pulling the trigger.

The cylindrical housing 14 is filled with sand to decelerate rounds which are fired therein. When the housing 14 is sufficiently full of bullets, the housing is turned  
5 upside down and the contents removed.

The configuration shown has several disadvantages. For example, the housing 14 must be made either of specially formed steel plate (i.e. steel having a thickness of 0.25 inches), or of standard steel. Forming the steel plate into  
10 the cylindrical housing 14 is expensive, and using standard steel raises the risk that the housing will become damaged if a user fires the gun at an angle significantly tangential to the long axis of the housing.

Additionally, cleaning the housing 14 is difficult as the  
15 housing must be inverted and the sand and bullets removed. The sand in the housing is heavy, thereby requiring significant strength to lift and invert the housing 14. Also, while the housing 14 is being cleaned, the trap 10 remains out of service.

20 In FIG. 1B, there is shown a side cross-sectional view of an alternate type of clearing trap, generally indicated at 30. The trap 30 uses a circular containment chamber 34 similar to that disclosed in U.S. Patent Nos. 5,070,763; 5,113,700;

5,121,671; and 5,486,008. As the bullet moves through from the opening 38 through the circular containment chamber 34, the bullet is forced to travel in a circular pattern. While such movement is highly effective at decelerating the bullet, it also tends to cause lead dust to be released into the air. Additionally, the trap 30 is relatively expensive to make, as plate steel must be formed into the circular pattern and be disposed in a relatively large housing.

FIG. 1C shows yet another trap, generally indicated at 50, which is used for clearing weapons. The trap has a housing 54 with an opening 58 for inserting a gun. Disposed within the housing 54 are a plurality of rubber sheets 60. As the bullet travels through the rubber sheets 60, the bullet is decelerated until it comes to a rest.

While the sheets are effective at stopping the bullet and preventing fragmentation, they also become riddled with holes due to the bullets and begin to fall apart. If used frequently, replacement of the sheets can be relatively expensive.

Thus, there is a need for an improved clearing trap and method for bullet deceleration which provides all of the advantages of prior art clearing traps without the disadvantages of the currently available systems. Such a



system should be inexpensive, easy to use, and ensure proper deceleration of bullets which are fired into the trap.

#### SUMMARY OF THE INVENTION

5           Thus, it is an object of the present invention to provide a clearing trap which is less expensive than those of the prior art.

          It is another object of the present invention to provide such a clearing trap which safety decelerates bullets.

10           It is still yet another object of the present invention to provide such a clearing trap which is easy to maintain, and has minimal downtime.

          The above and other objects of the invention are realized in specific illustrated embodiments of a clearing trap having  
15           a housing, a bullet deceleration insert, and a bullet decelerating material disposed within the insert for decelerating bullets fired into the trap.

          In accordance with one aspect of the invention, the housing is formed of a conventional grade steel which is  
20           preformed in a desired shape (typically of square cross-section). The insert is formed of a plate steel which is sufficiently thick to stop high-power or other predetermined strength rounds. The insert may be slid into the housing for

use, and then slid out of the housing when the insert becomes sufficiently full to require emptying. While the insert is being cleaned, another insert can be placed into the housing so that there is virtually no downtime for the clearing trap.

5 In accordance with another aspect of the invention, the insert is formed from interlocking pieces of plate steel. To empty the insert, one piece must simply be moved relative to another, thereby exposing the contents of the insert and allowing for rapid cleaning and refilling of the insert.

10 In accordance with still yet another aspect of the invention, the insert is provided with a plurality of vent holes. The vent holes are configured to allow release of a small amount of air from the insert when a gun is fired into the insert - thereby dissipating the energy associated with  
15 firing the gun.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and advantages of the invention will become apparent from a consideration of the  
20 following detailed description presented in connection with the accompanying drawings in which:

FIG. 1A shows a side view of a clearing trap made in accordance with the teachings of the prior art;

FIG. 1B shows a side cross-sectional view of another clearing trap made in accordance with the teachings of the prior art;

FIG. 1C shows a side cross-sectional view of another clearing trap made in accordance with the teachings of the prior art;

FIG. 2 shows a side view of a clearing trap made in accordance with the principles of the present invention, and a gun inserted into the clearing trap;

FIG. 3 shows a side cross-sectional view of the clearing trap shown in FIG. 2;

FIG. 4 shows a disassembled top view of a bullet deceleration insert for use in the clearing trap shown in FIGs. 2 and 3; and

FIG. 5A shows a plan view of a pair of end plates disposed at the end of an insert made in accordance with principles of the present invention;

FIG. 5B shows a fragmented side view of the housing, with the orientation of the end plates demonstrated in shadow; and

FIG. 6 shows an end view of the bottom wall and sidewalls of an insert with a different end plate configuration attached thereto.

## DETAILED DESCRIPTION

Reference will now be made to the drawings in which the various elements of the present invention will be given numeral designations and in which the invention will be discussed so as to enable one skilled in the art to make and use the invention. It is to be understood that the following description is only exemplary of the principles of the present invention, and should not be viewed as narrowing the pending claims.

FIG. 2 shows a side view of a clearing trap, generally indicated at 100, made in accordance with the principles of the present invention. The clearing trap 100 includes an elongate housing 104 into which a gun 108 is inserted and the trigger pulled in order to ensure that the gun has been properly unloaded. The housing 104 is typically formed by an outer wall surrounding a void.

A pair of flanges 112 and 114 are positioned adjacent the top of the housing 104. The flanges 112 and 114 extend outwardly 104 and hold a rubber shield 116 to form a face plate with an opening for receiving the gun 108. As will be explained in additional detail below, the flanges 112 and 114 can be attached directly to the housing 104 or to an insert (not shown) which nests within the housing.

The housing 104 is preferably made of a tube of conventional steel having a square cross-section. The housing 104 is disposed at an angle of between about 50 and 70 to the horizontal so that the user may maintain a comfortable position when performing the clearing check on the gun 108.

The housing 104 is supported by a leg 120 which prevents the housing from being accidentally pulled toward the user. A base plate 124 is attached to the bottom the housing 104 and the leg 120 to provide lateral stability. For reasons which are discussed in additional detail below, the base plate 124 can be anchored to the floor by bolts or some other securement mechanism if desired.

Turning now to FIG 3, there is shown a cross-sectional view of the housing 104 of FIG. 2. A bullet deceleration insert 130 is disposed in the housing 104 and extends substantially the length thereof. The bullet deceleration insert 130 is preferably slidably removable from the housing 104 by pulling the insert upwardly along the long axis of the housing. While the housing 104 is typically made of steel, it can also be made of other materials, such as plastic, wood, etc. The housing 104 may be made from materials other than those conventionally used for bullet deceleration because the insert 130 is made from steel which is sufficiently hard and

thick (i.e 0.25 inch plate steel) to withstand a desired round. Because the insert 130 decelerates the bullet, the housing 104 does not have to withstand a significant amount of force.

5 As shown in FIG. 3, the insert 130 is filled with a bullet deceleration medium 134, such a chopped pieces of rubber, which preferably decelerates the bullet before it reaches the lower end 130a of the insert. At the opposing upper end 130b, the insert 130 may be attached to the flanges 10 112 and 114 and rubber shield 116 forming the face plate so that the flanges 112 and 114 form a stop which limits advancement of the insert into the housing 104. In the alternative, the housing 104 can simply be sized so that the insert 130 can only be advanced a predetermined distance into the housing 104 before being stopped by the base plate 124 or 15 some other obstruction.

While not shown in FIG. 3, the insert may also include a plurality of vents. The vents allow the force produced by firing a round at close range to be more readily dissipated. 20 If any deceleration medium 134 escapes from the insert 130 through the vents, it will simply collect at the bottom of the housing 104 and may be cleaned out at a later time by use of a vacuum, shovel, etc.

Also discussed in detail below with respect to a preferred embodiment of the insert 130 is that one wall of the insert can be removed from the remaining portions to facilitate rapid cleaning of the insert. When such a configuration is used, the removable wall is disposed adjacent the upper sloping sidewall 104a of the housing 104. In such a configuration, the upper wall of the insert 130 is unlikely to accidentally open under the weight of the bullet deceleration medium 134 and bullets contained therein.

Turning now to FIG. 4, there is shown a partially disassembled top view of the insert 130. The insert 130 is preferably formed by a bottom portion 138 comprising a bottom wall 140 and a pair of sidewalls 144 attached to the bottom wall so as to form a U-shaped cross-section. Ideally, the sidewalls 144 are connected to the bottom wall 140 by a plurality of interlocking channels 146 and tabs 148. The bottom wall 140 is then welded to the sidewalls 144 to form a three sided container. An end plate 152 is disposed on the lower end 130a of the insert 130 and is preferably welded to the bottom wall 140 and the sidewalls 144. The end plate 152 can be formed from a solid piece of plate or, as is explained below, may be formed from overlapping plates with slots which provide vents for the insert 130.

Also shown in FIG. 4 is the top wall 156. Unlike the bottom wall 140 and the sidewalls 144, the top wall 156 is not welded to the remaining portions of the insert 130. Rather, the top wall 156 has tabs 160 and channels 164 which engage the channels 146 and tabs 148 of the sidewalls 144 to facilitate attachment to the bottom portion 138. Preferably, the tabs and channels 146, 148, 160 and 164 engage one another to leave a plurality of small vents along the insert 130. The vents allow a small amount of air to escape the insert 130 to dissipate the force associated with firing a gun into the insert, but are sufficiently small that a bullet could not pass therethrough without obliterating the bullet.

The insert 130 embodiment shown in FIG. 4 is a presently preferred embodiment because, by having the top 156 readily removable from the sidewalls 144, the insert 130 can be opened and cleaned with very little effort. Once returned to its place, however, the top 156 securely engages the sidewalls 144 and the insert 130 forms a highly effective bullet trap. While providing less efficient cleaning, the insert could be formed with all four plates fixedly attached to each other to form a tubular insert closed at the bottom by the end plate 152.

One principle advantage of the configuration of the



present invention is that it is generally of lower cost than the prior art. Because the housing 104 does not need to be extremely bullet resistant, off-the-shelf square tubing can be used. While the steel plate necessary to make the insert 130 is generally expensive, the relatively small sizes which are used for the bottom 140, sidewalls 144 and top 156 are readily obtainable from scrap left over from cutting larger pieces of plate for full sized bullet containment traps. Thus, the primary costs associated with the clearing trap 100 are the labor to cut the pieces and weld them together.

Turning now to FIGs. 5A, there is shown a bottom view an end plate 152' made in accordance with principles of the present invention. While the lower end 130a of the insert 130 can be formed by a solid end plate 152 as discussed above, it is preferably formed by a pair of plates. A first plate 152A (which is shown in shadow in FIG. 5A) is configured with three slots 170 therein. A second plate 152B is configured with four slots 174 therein. As shown in FIG. 5A, when the first and second plates 152A and 152B are oriented so that the slots 170 and 174 are parallel, the slots do not overlap. Thus, there is no straight line which a projectile could follow and pass through both the slots 170 in the first plate 152A and the slots 174 in the second plate 152B.

FIG. 5B shows a side view of the housing 104 with the insert 130, including the end plate 152' shown in shadow. Preferably, the first plate 152A and the second plate 152B are also spaced apart slightly when they are welded to the bottom 140 and sidewalls 144. This spacing allows airflow to pass through the slots 170 and 174 while substantially eliminating the probability of a bullet passing through slots. Of course, the narrower the slots 170 and 174, the less the likelihood that a bullet would pass therethrough. Furthermore, it is important to remember that very few bullets will ever reach the end plate 152' due to the bullet deceleration medium 134 (FIG. 3) disposed in the insert.

While the configuration shown in FIG. 5A and 5B is a preferably preferred embodiment, the first and second plates 152A and 152B could be rotated so that the slots 170 and 174 overlap one another, thereby leaving small holes in the bottom plate 152 to allow air flow, yet substantially prevent bullet fragments from passing therethrough.

FIG. 6 shows an end view of the bottom wall 140' and sidewalls 144' of an insert 130'. Unlike the insert discussed above, the bottom wall 140', the sidewalls 144', and the top wall 156' are simply welded together. While such a configuration does not provide vents, vents could be provided

if desired by either forming grooves into the edges of the bottom wall 140', sidewalls 144' or top wall 156', or by drilling holes in the walls.

5 Disposed at the far end of the insert 130' is a single end plate 152''. The end plate 152'' has six small slots 170' formed therein to provide venting of the insert. By providing vents, the force of generated by discharging the gun is dissipated and the risk of the force blowing bullet deceleration medium 134 (FIG. 3) back at the user is  
10 minimized.

Thus there is disclosed an improved clearing trap for use with firearms which is inexpensive, easy to construct and to use. While the embodiment shown in FIGs. 2 through 6 are currently preferred embodiments, those skilled in the art will  
15 appreciate that numerous modifications can still be made within the principles of the present invention. For example, while a square cross-section is presently preferred for the housing 104 and the insert 130 or 130' because plate pieces of steel plate are readily available, the housing and the insert  
20 could be formed with some other cross-sectional geometry. Likewise, those skilled in the art will appreciate that numerous other modifications could be made to the invention with respect to the vents or other aspects of the housing 104



## CLAIMS

1. A trap for receiving bullets, the trap comprising:  
a housing having a cavity defined by an outerwall  
surrounding a void; and

5 an insert forming a bullet deceleration chamber, the  
insert being slidably insertable into and removable from the  
void of the housing.

2. The trap for receiving bullets according to claim 1,  
10 wherein the insert is formed by a plurality of pieces of steel  
plate.

3. The trap for receiving bullets according to claim 2,  
wherein the plurality of pieces of steel plate form a bottom  
15 portion having a generally u-shaped cross-section and a top  
removably engaging the bottom portion such that the insert has  
a square cross-section when the top is attached.

4. The trap for receiving bullets according to claim 3,  
20 wherein the bottom portion is formed by a bottom and a pair of  
sidewalls, the bottom and sidewalls being fixedly attached to  
one another.

5. The trap for receiving bullets according to claim 1, wherein the insert comprises a plurality of vents for releasing force from the insert when a gun is fired into the insert.

5

6. The trap for receiving bullets according to claim 5, wherein the insert is formed from a top plate, a bottom plate and a pair of sidewalls, and wherein the vents are formed between the sidewalls and at least one of the top plate and the bottom plate.

10

7. The trap for receiving bullets according to claim 5, wherein the insert has at least one plate forming a lower end, and wherein the at least one plate has at least one slot formed therein.

15

8. The trap for receiving bullets according to claim 7, wherein the insert has two bottom plates and wherein the bottom plates each have slots formed therein.

20

9. The trap for receiving bullets according to claim 8, wherein the plates are aligned such that the slots in the plates do not overlap.

10. The trap for receiving bullets according to claim 1, wherein the insert further comprises a bullet deceleration medium disposed therein.

5           11. The trap for receiving bullets according to claim 10, wherein the bullet deceleration medium is formed by pieces of rubber.

10           12. The trap for receiving bullets according to claim 1, wherein the housing is formed from a tube having a generally square cross-section.

15           13. The trap for receiving bullets according to claim 1, wherein the housing is formed from a material other than plate steel.

14. A clearing trap for receiving bullets fired from a gun, the clearing trap comprising:

20           a housing having an outerwall and a void disposed within the outerwall; and

            an insert disposed in the void of the housing, the insert forming a bullet deceleration chamber and having at least one vent formed therein.

15. The clearing trap according to claim 14, wherein the insert is slidably removable from the housing.

16. The clearing trap according to claim 14, wherein the insert is formed by a bottom portion and a top portion, the top portion being removable from the bottom portion.

17. The clearing trap according to claim 14, wherein the insert is filled with a removable bullet deceleration medium.

18. The clearing trap according to claim 14, further comprising a leg attached to the housing for supporting the housing.

19. The clearing trap according to claim 18, further comprising a base plate attached to the housing and the leg.

20. A method for forming a clearing trap, the method comprising;

selecting a housing having a void configured to receive a bullet deceleration chamber;

selecting a bullet deceleration chamber; and

sliding the bullet deceleration chamber into the void



configured to receive the bullet configuration.

21. The method according to claim 20, wherein the method  
former comprises forming a face plate at one end of the  
housing or insert.

22. The method according to claim 20, wherein the method  
further comprises filling the bullet deceleration chamber with  
a bullet deceleration medium.

23. The method according to claim 20, wherein the method  
comprises, forming the bullet deceleration chamber from a  
plurality of generally flat pieces of steel.

24. The method according to claim 23, further comprising  
fixedly attaching a plurality of the generally flat pieces of  
steel, and releasably attaching at least one of the generally  
flat pieces of steel to the plurality of generally flat pieces  
of steel which are fixedly attached.

25. The method according to claim 20, wherein the method  
comprises forming a plurality of vents in the bullet  
deceleration chamber.

# ABSTRACT OF THE DISCLOSURE

A clearing trap for decelerating bullets includes a housing and a bullet decelerating insert disposed within the housing. Preferably, the insert is slidably removable from the housing and is provided with a plurality of vents which help dissipate the force associated with firing a gun into a small enclosure. Also preferably, a portion of the insert is detachable or openable to facilitate periodic cleaning of the insert.




FIG. 1A  
(Prior Art)




FIG. 1B  
(Prior Art)

FIG. 1C  
(Prior Art)




FIG. 2




Fig. 3




FIG. 4








FIG. 6

